




ERF8-FSFS3B-03BPUR

M8 Female, 0° Straight, Female, 0° Straight, 3 Pin, PUR, 03 Meters, $3x0,34\,$ mm²


















Technical Data

| Standard | IEC 61076 | Contact Carriers Material | PU / PA | |
|-----------------------|----------------------|---------------------------|---------------------------------|--|
| Series | M8, Female, Straight | Contact Material | Copper Alloy, Gold-Plated | |
| Number of Pins | 03 Pin | Metal of Nut | Copper Alloy with Nickel Plated | |
| Rated Current | 3A max. | Seal | Silicone | |
| Rated Voltage | 60V max. | Cable Jacket Material | PUR | |
| Insulation Resistance | ≥100MΩ | Color | Optional | |
| Contact Resistance | ≤ -5mΩ | Shielding | Optional | |
| Ambient Temperature | -25 ~ +75°C | Mechanical Life | > 100 Mating Cycles | |
| IP Class | IP67 | _ | _ | |
| | | | | |

| ARTICLE NO | TYPE | ANGLE | PIN | CABLE LENGTH | COLOR | CABLE TYPE | CABLE SECTION |
|--------------------|------|-------|-------|--------------|-------|------------|--------------------------|
| ERF8-FSFS3B-03BPUR | F-F | S - S | 3 PİN | 3 METERS | BLACK | PUR | 3 x 0,34 mm ² |

