



# ERF0B-FA3E-06B-24Y-PVC

B-10 mm Led Valve Connector, 3 Pin, PVC,  
06 Meters, 3x0,75 mm<sup>2</sup>



Technical Data

|                       |                |                           |                                 |
|-----------------------|----------------|---------------------------|---------------------------------|
| Standard              | IEC 61076      | Contact Carriers Material | CU / AU                         |
| Series                | Female, Angled | Contact Material          | Copper Alloy, Gold-Plated       |
| Pin                   | Cu / Au        | Metal of Nut              | Copper Alloy with Nickel Plated |
| Rated Current         | 3A max.        | Seal                      | Silicone                        |
| Rated Voltage         | 60V max.       | Cable Jacket Material     | PVC                             |
| Insulation Resistance | ≥100MΩ         | Color                     | Optional                        |
| Contact Resistance    | ≤ -5mΩ         | Shielding                 | Optional                        |
| Ambient Temperature   | -25 ~ +75°C    | Mechanical Life           | > 100 Mating Cycles             |
| IP Class              | IP67           | —                         | —                               |

| ARTICLE NO             | TYPE       | ANGLE      | PIN   | CABLE LENGTH | COLOR        | CABLE TYPE | CABLE SECTION            |
|------------------------|------------|------------|-------|--------------|--------------|------------|--------------------------|
| ERF0B-FA3E-06B-24Y-PVC | F - FEMALE | A - ANGLED | 3 PIN | 6 METERS     | BLACK / GREY | PVC        | 3 x 0,75 mm <sup>2</sup> |