



# ERF12-FS12D-15BPUR

M12 Female, 0° Straight, 12 Pin, PUR, 15 Meters, 12x0,14 mm<sup>2</sup>



- White
- Brown
- Green
- Yellow
- Grey
- Pink
- Blue
- Red
- Black
- Navy



### Technical Data

Standard	IEC 61076	Contact Carriers Material	PU / PA
Series	M12, Female, Straight	Contact Material	Copper Alloy, Gold-Plated
Number of Pins	12 Pin	Metal of Nut	Copper Alloy with Nickel Plated
Rated Current	2A max.	Seal	Silicone
Rated Voltage	60V max.	Cable Jacket Material	PUR
Insulation Resistance	≥100MΩ	Color	Optional
Contact Resistance	≤ -5mΩ	Shielding	Optional
Ambient Temperature	-25 ~ +75°C	Mechanical Life	> 100 Mating Cycles
IP Class	IP67	—	—

ARTICLE NO	TYPE	ANGLE	PIN	CABLE LENGTH	COLOR	CABLE TYPE	CABLE SECTION
ERF12-FS12D-15BPUR	F - FEMALE	S - STRAIGHT	12 PIN	15 METERS	BLACK	PUR	12 x 0,14 mm <sup>2</sup>