


ERF12P-FS8C-0,5PVC

M12 Female, 0° Straight, 8 Pin, PVC,
0,5 Meters, 8x0,22 mm²





- White
- Brown
- Green
- Yellow
- Grey
- Pink
- Blue
- Red



RoHS COMPLIANT · 48 H SALT SPRAY · IP67

Technical Data

Standard	IEC 61076	Contact Carriers Material	PU / PA
Series	M12, Female, Straight	Contact Material	Copper Alloy, Gold-Plated
Number of Pins	08 Pin	Metal of Nut	Copper Alloy with Nickel Plated
Rated Current	4,5A max.	Seal	Silicone
Rated Voltage	60V max.	Cable Jacket Material	PVC
Insulation Resistance	≥100MΩ	Color	Optional
Contact Resistance	≤ -5mΩ	Shielding	Optional
Ambient Temperature	-25 ~ +75°C	Mechanical Life	> 100 Mating Cycles
IP Class	IP67	—	—

ARTICLE NO	TYPE	ANGLE	PIN	CABLE LENGTH	COLOR	CABLE TYPE	CABLE SECTION
ERF12P-FS8C-0,5PVC	F - FEMALE	S - STRAIGHT	8 PİN	0,5 METERS	BROWN-BLUE-BLACK	PVC	8 x 0,22 mm²