



# ERF8-FAFA4B-03BPVC

M8 Female, 90° Angled, Female, 90° Angled, 4 Pin, PVC, 03 Meters, 4x0,34 mm<sup>2</sup>



4 PIN FEMALE



## Technical Data

|                       |                    |                           |                                 |
|-----------------------|--------------------|---------------------------|---------------------------------|
| Standard              | IEC 61076          | Contact Carriers Material | PU / PA                         |
| Series                | M8, Female, Angled | Contact Material          | Copper Alloy, Gold-Plated       |
| Number of Pins        | 04 Pin             | Metal of Nut              | Copper Alloy with Nickel Plated |
| Rated Current         | 3A max.            | Seal                      | Silicone                        |
| Rated Voltage         | 60V max.           | Cable Jacket Material     | PVC                             |
| Insulation Resistance | ≥100MΩ             | Color                     | Optional                        |
| Contact Resistance    | ≤ -5mΩ             | Shielding                 | Optional                        |
| Ambient Temperature   | -25 ~ +75°C        | Mechanical Life           | > 100 Mating Cycles             |
| IP Class              | IP67               | —                         | —                               |

| ARTICLE NO         | TYPE  | ANGLE | PIN   | CABLE LENGTH | COLOR | CABLE TYPE | CABLE SECTION            |
|--------------------|-------|-------|-------|--------------|-------|------------|--------------------------|
| ERF8-FAFA4B-03BPVC | F - F | A - A | 4 PIN | 3 METERS     | BLACK | PVC        | 4 x 0,34 mm <sup>2</sup> |